

## ABSTRACT

When a network pages the temporary user mobile identifier of a mobile station, the mobile station sends a response to the network. Next, the network checks the authenticity of the user using a ciphering key, corresponding to the temporary user mobile identifier and a random number. If the temporary user mobile identifier is authenticated, a normal incoming call acceptance procedure is executed. If the mobile station is authenticated although the temporary user mobile identifier is wrong, the network reassigns a new temporary user mobile identifier to the mobile station and stops the current communication. In communication, the network and the mobile station mutually notify encipherment-onset time and negotiate about encipherment manner with each other. In addition, diversity handover is commenced upon a call attempt. Furthermore, if a branch replacement is necessary, the current branch is replaced by new branches capable of executing the diversity handover. Additionally, when a new call occurs to or from the mobile station capable of treating a plurality of calls simultaneously, the mobile station uses the same branch structure and the same communication frequency band for all of calls. Additionally, when a new call occurs to or from the mobile station capable of treating a plurality of calls simultaneously, a branch structure and a communication frequency band, which can continue all of the calls, are selected and used. Therefore, the mobile communications system is suitable for transmission of various sorts of data in accordance with the development of multimedia.

2025 RELEASE UNDER E.O. 14176



<p>(51) 国際特許分類6 H04B 7/26, H04Q 7/24</p>	<p>A1</p>	<p>(11) 国際公開番号 WO98/48528</p> <p>(43) 国際公開日 1998年10月29日(29.10.98)</p>
<p>(21) 国際出願番号 PCT/JP98/01906</p> <p>(22) 国際出願日 1998年4月24日(24.04.98)</p> <p>(30) 優先権データ 特願平9/123782 1997年4月24日(24.04.97)</p> <p>(71) 出願人 (米国を除くすべての指定国について) エヌ・ティ・ティ移動通信網株式会社 (NTT MOBILE COMMUNICATIONS NETWORK INC.)[JP/J] 〒105-8436 東京都港区虎ノ門二丁目10番1号 Tokyo, (JP)</p> <p>(72) 発明者 ; および (75) 発明者 / 出願人 (米国についてのみ) 田村 基(TAMURA, Motoshi)[JP/J] 〒239-0841 神奈川県横浜須賀野市野比4丁目18-2-101 Kanagawa, (JP) 三木睦丸(MIKI, Mutsumaru)[JP/J] 〒239-0841 神奈川県横浜須賀野市野比4丁目18-2-105 Kanagawa, (JP) 中島亜紀子(NAKASHIMA, Akiko)[JP/J] 〒814-0015 福岡県福岡市早良区室見1丁目2-2 コンドミニウム室見駅アベニュー803号 Fukuoka, (JP) 楠瀬賢也(KUSUNOSE, Kenya)[JP/J] 〒239-0847 神奈川県横浜須賀野市光の丘6-1-302 Kanagawa, (JP) 打越昭宏(UCHIKOSHI, Akihiro)[JP/J] 〒239-0841 神奈川県横浜須賀野市野比4丁目18-2-304 Kanagawa, (JP) 五十嵐大輔(IGARASHI, Daisuke)[JP/J] 〒239-0847 神奈川県横浜須賀野市光の丘6-1-508 Kanagawa, (JP) 山縣克彦(YAMAGATA, Katsuhiko)[JP/J] 〒247-0007 神奈川県横浜須賀野市栄小菅ヶ谷1-22-3-302 Kanagawa, (JP)</p>	<p>佐藤隆明(SATO, Takaaki)[JP/J] 〒221-0861 神奈川県横浜市神奈川区片倉町79-3 ビケンアーバンス405 Kanagawa, (JP) 萩原淳一郎(HAGIWARA, Junichiro)[JP/J] 〒237-0063 神奈川県横浜須賀野市追浜東町1-7-1 ポートビルⅡ-305 Kanagawa, (JP) 渡邊靖之(WATANABE, Yasuyuki)[JP/J] 〒235-0033 神奈川県横浜須賀野市磯子区杉田9-2-8-202 Kanagawa, (JP) 濱島拓也(HAMAJIMA, Takuya)[JP/J] 〒237-0071 神奈川県横浜須賀野市田浦港町1283-3 マリンハイム606 Kanagawa, (JP) 秦 正史(HATA, Masafumi)[JP/J] 〒238-0012 神奈川県横浜須賀野市安浦町1-8 ダイカンプラザシティ-3-301 Kanagawa, (JP) 石川信能(ISHIKAWA, Nobutaka)[JP/J] 〒236-0053 神奈川県横浜須賀野市金沢区能見台通18-11 ベルライト能見台202 Kanagawa, (JP) 保田佳之(YASUDA, Yoshiyuki)[JP/J] 〒235-0021 神奈川県横浜須賀野市磯子区岡村6-13-31 Kanagawa, (JP) 柚木一文(YUNOKI, Kazufumi)[JP/J] 〒239-0841 神奈川県横浜須賀野市野比4丁目18-4-304 Kanagawa, (JP) 内山伸英(UCHIYAMA, Nobuhide)[JP/J] 〒239-0841 神奈川県横浜須賀野市野比4丁目18-4-1101 Kanagawa, (JP)</p> <p>(74) 代理人 弁理士 川崎研二, 外(KAWASAKI, Kenji et al.) 〒103-0027 東京都中央区日本橋三丁目2番16号 八重洲マスマビル5階 朝日特許事務所 Tokyo, (JP)</p> <p>(81) 指定国 CA, CN, JP, KR, US, 欧州特許 (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>添付公開書類 国際調査報告書</p>	

(54) Title: **MOBILE COMMUNICATION METHOD AND MOBILE COMMUNICATION SYSTEM**

(54) 発明の名称 移動通信方法及び移動通信システム

### (57) Abstract

When a network performs paging by using a temporary mobile user identifier (TMUI), the corresponding mobile station (MS) sends a response. After this, the network performs authentication by using an authentication key corresponding to the TMUI and random numbers. When the use is proved to the unauthorized as a result of the authentication, the network sends a request that the user should send an individual mobile user identifier (IMUI). Then, the network performs authentication by using an authentication key corresponding to the IMUI and random numbers (S8-S10). When the user is identified as an authorized user, the TMUI is allocated again. By negotiation between the MS and the network side, the object to be hidden and the hiding method for controlling the hiding start timing included in the information to be transmitted are determined. When a call occurs, a diversity handover is started. When a branch switching is needed at an MS, the branch is switched over to a branch through which diversity handover is possible. When another call takes place at an MS that can deal with a plurality of calls simultaneously, the branch configurations and communication frequency bands are made the same for all the calls. When another call occurs at an MS that can deal with a plurality of calls simultaneously, branch configurations and communication frequency bands for which all of the calls are maintained are selected, and transition to them is performed. Thus, a mobile communication system can be built which is suited for transmitting various kinds of data, thereby being adapted to multimedia communication.

